

# AFL-508V2



8Ch Universal Digital Video Recorder (5brid: TVI, AHD, CVI, 960H, IP)

WE'RE ALWAYS WATCHING®



## Features

- 4K UHD Display (HDMI)
- Support TVI, AHD, CVI, 960H, IP
- 2MP, 4MP: 8 Channel BNC Inputs + 4 IP  
4K: 4 Channel BNC Inputs + 1 IP
- Support ONVIF
- Support Ethernet POS
- Up to 2HDDs or (1HDDs + 1eSATA)
- Network Interface - 2x Ethernet 10/100/1G
- Smartphone Viewer Support (Android/iPhone/iPad)



(8ch) BNC Input + (4ch) IPC

## Specifications

| AFL-508V2          |                                 |
|--------------------|---------------------------------|
| <b>VIDEO</b>       |                                 |
| Input              | 8 BNC                           |
| Input Resolution   | 8MP, 4MP, 3MP, 2MP, 960H        |
| Output             | 1 HDMI, 1VGA, 2BNC (1 HD, 1 SD) |
| Output Resolution  | 4K, FHD, SXGA, XGA              |
| <b>RECORDING</b>   |                                 |
| Speed              | 15fps/ch(4MP), 30fps/ch(2MP)    |
| Resolution         | 8MP, 4MP, 3MP, 2MP, 960H        |
| <b>AUDIO</b>       |                                 |
| Input              | 4 RCA                           |
| Output             | 1 HDMI, 1 RCA                   |
| <b>INTERFACE</b>   |                                 |
| Sensor In / Out    | 4 / 1 - NC / NO                 |
| USB                | 2 x USB 2.0                     |
| PTZ / Keyboard     | 2 x RS485 - Terminal Block      |
| ATM / POS          | Ethernet POS                    |
| <b>NETWORK</b>     |                                 |
| Interface          | 2 x Ethernet 10/100/1G          |
| Compression        | H.264, JPEG                     |
| Speed              | 10fps(4MP), 20fps(2MP)          |
| Resolution         | Max. 4MP                        |
| <b>STORAGE</b>     |                                 |
| Primary / External | 2 HDD or (1 HDD + 1 eSATA)      |

| SYSTEM            |   |
|-------------------|---|
| OS                | Embedded Linux (Built-in Flash Memory)                                    |
| Pre / Post-Alarm  | 5sec / 5sec~5min  |
| Recording Mode    | Continuous, Event, Schedule   |
| Data Search       | Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time            |
| Backup Interface  | USB, Network  |
| Backup Type       | Video(RMS, AVI), Capture(JPEG), Log List, Setup Data                      |
| Alarm Action      | Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push |
| User              | 15 Users (Admin, User1 ~ User14)  |
| Network Viewer    | Netus, VMS, Web Viewer, Mac Viewer, ACT VIEW HD (iOS, Android)            |
| ONVIF             | ONVIF Profile S   |
| <b>GENERAL</b>    |   |
| Dimensions        | 340 x 60 x 300 mm   |
| Weight(w/o HDD)   | 3kg   |
| Temp / Humidity   | 5 ~ 40°C / 10% ~ 80%  |
| Power Supply      | 12V / 3.3A  |
| Power Consumption | 40 Watts  |